



M285

Lithium-ion Battery Pack

System Voltage: 24V

Nominal Voltage: 25.76V

Capacity: 228Ah

Kilowatt Hour: 5.87kWh

Application: Material Handling

DETAILS

M285

Lithium-ion Battery Pack Details:

ULBS M285 battery pack provides end-users with the ability to upgrade their existing lead-acid powered equipment with a Lithium Iron Phosphate (LiFePO₄) battery pack. This battery chemistry is the balance between being the safest, most reliable, and best performing lithium-ion chemistry on the market. Combined with the proprietary BMS and durable battery pack case, ULBS ensures that the M285 battery pack is the safe and reliable upgrade that an end-user needs when looking at new power solutions for their equipment.

ULBS Battery Packs Feature:

- Longer Run Times
- Rapid Charging using a ULBS Charger
- Opportunity Charging
- No Maintenance
- Substantial Return on Investment in Most Applications

SPECIFICATIONS

M285 Lithium-ion Battery Pack Specifications

ULBS Model Number	DQ-25.76-228-UBM285
System Voltage	24V
Nominal Voltage	25.76V
Capacity	228Ah
Kilowatt Hour	5.87kWh
Application	Material Handling
W×L×H(Inch)	24.50×11.00×24.00
Weight	551lbs
Operating Voltage Range	20.0V~28.8V
Maximum charge current	30A
Continuous discharge current	≤228A(SOC ≥ 20%, 77°F)
Charging Operating Temperature	32~131°F
Discharging Operating Temperature	-18~131°F
Cycle life	>4000
Built-in charger	Y



Universal Lithium-ion Battery Supply