



M296

Lithium-ion Battery Pack

System Voltage: 24V
Nominal Voltage: 25.60V
Capacity: 210Ah
Kilowatt Hour: 5.38kWh
Application: Material Handling

DETAILS

M296

Lithium-ion Battery Pack Details:

ULBS M296 battery pack provides end-users with the ability to upgrade their existing lead-acid powered equipment with a Lithium Iron Phosphate (LiFePO₄) battery pack. This battery chemistry is the balance between being the safest, most reliable, and best performing lithium-ion chemistry on the market. Combined with the proprietary BMS and durable battery pack case, ULBS ensures that the M296 battery pack is the safe and reliable upgrade that an end-user needs when looking at new power solutions for their equipment.

ULBS Battery Packs Feature:

- Longer Run Times
- Rapid Charging using a ULBS Charger
- Opportunity Charging
- No Maintenance
- Substantial Return on Investment in Most Applications

SPECIFICATIONS

M296 Lithium-ion Battery Pack Specifications

ULBS Model Number	DQ-25.6-210-UBM296
System Voltage	24V
Nominal Voltage	25.60V
Capacity	210Ah
Kilowatt Hour	5.38kWh
Application	Material Handling
W×L×H(Inch)	33.59×6.20×23.25
Weight	172lbs
Operating Voltage Range	20.0V~28.8V
Maximum charge current	30A
Continuous discharge current	≤210A(SOC ≥ 20%, 77°F)
Charging Operating Temperature	32~131°F
Discharging Operating Temperature	-18~131°F
Cycle life	>4000
Built-in charger	Y



Universal Lithium-ion Battery Supply